

## Product information sheet

**Supplier's name or trade mark:** AKKONAK YAPI AYDINLATMA SANAYİ VE TİCARET A.Ş.  
( Trade mark : ATLANTIS AYDINLATMA )

**Supplier's address** <sup>(1)</sup>: ZİRVE SOK. No:6/A 34785 EMEK MAH./SANCAKTEPE/İSTANBUL

**Model identifier:** A60-4W-2700K

**Type of light source:** LED Filament Bulb


Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	NO
Colour-tuneable light source:	NO	Envelope:	NO
High luminance light source:	NO		
Anti-glare shield:	NO	Dimmable:	YES

### Product parameters

Parameter	4W	Parameter	2700K
-----------	----	-----------	-------

### General product parameters:

Energy consumption in on-mode (kWh/1 000 h)	4W	Energy efficiency class	F
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	420LM	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated	2700K

		colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode power ( $P_{on}$ ), expressed in W	4W	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	NO
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	NO	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	60	Spectral power distribution in the range 250 nm to 800 nm, at full-load 
	Width	60	
	Depth	108	
Claim of equivalent power <a href="#">(3)</a>	Yes	If yes, equivalent power (W)	30W
		Chromaticity coordinates (x and y)	x=0.4631                      y=0.4189
<b>Parameters for directional light sources:</b>			
Peak luminous intensity (cd)	N/A	Beam angle in degrees, or the range of beam angles that can be set	360°

*Parameters for LED and OLED light sources:*

R9 colour rendering index value	8	Survival factor	0.9
the lumen maintenance factor	0.95		

*Parameters for LED and OLED mains light sources:*

displacement factor (cos $\phi$ 1)	0.5	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	NO	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0.2	Stroboscopic effect metric (SVM)	0.2

