

Product information sheet

Supplier's name or trade mark: AKKONAK YAPI AYDINLATMA SANAYİ VE TİCARET A.Ş. (Trade mark : ATLANTIS AYDINLATMA)			
Supplier's address (†): ZİRVE SOK. No:6/A 34785 EMEK MAH./SANCAKTEPT/İSTANBUL			
Model identifier: G125-4W-2500K			
Type of light source: LED Filament Bulb			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	NO
Colour-tuneable light source:	NO	Envelope:	NO
High luminance light source:	NO		
Anti-glare shield:	NO	Dimmable:	YES
Product parameters			
Parameter	4W	Parameter	2500K
General product parameters:			
Energy consumption in on-mode (kWh/1 000 h)	4W	Energy efficiency class	F
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	360 lm	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2500K
On-mode power (P_{on}), expressed in W	4W	Standby power (P_{sb}), expressed in W and rounded to the second decimal	N/A
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	NO	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80

Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	125	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
	Width	125		
	Depth	176		
Claim of equivalent power (3)		YES	If yes, equivalent power (W)	26W
			Chromaticity coordinates (x and y)	x=0.4826 y=0.4226
Parameters for directional light sources:				
Peak luminous intensity (cd)		N/A	Beam angle in degrees, or the range of beam angles that can be set	360°
Parameters for LED and OLED light sources:				
R9 colour rendering index value		1	Survival factor	0,90
the lumen maintenance factor		0,95		
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)		0,5	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		NO	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0.2	Stroboscopic effect metric (SVM)	0.2



ATLANTIS AYDINLATMA
G125-4W-2500K

A

B

C

D

E

F

G

←

F

4
kWh / 1000h



2019/2015